

Wired Controller Compatibility Chart



Wired Controller Series	Part Code	Description	Sapphire	All Vireo & Vireo ULTRA	All Livo
XE71	MC20700970	Single/Multi zone programmable controller with touch pad & back light. Includes 26 ft. wire harness Part # 4003800101 with Molex plugs.	✓	✓	✓
XK41 (Obsolete) (Replaced by XE71)	GREEMC207059	Single/Multi zone High-Wall programmable controller with touch pad & back light. Includes 26 ft. wire harness Part # 4003800101 with Molex plugs.	✓	✓	✓
XK76	MC20700360	Single/Multi zone programmable controller with touch pad & back light. Includes (1) 26 ft. & (1) 6.5 in. harness Part # 4003800101 & 4001024512 with Molex plugs.	✓	✓	✓



XE71



XE72 WIFI



XK19



XK76 & XK60

Wired Controller Series	Part Code	Description	Multi Cassette	Multi Slim Duct	Multi Floor/Ceiling	Multi Mini-Console	U-Match Cassette /Floor-Ceiling /Slim Duct	U-Match Mini-Console
XK19	MC20700140	Used with all Multi Zones - programmable controller with touch buttons. Includes 26 ft. wire harness Part # 40010232 with Molex plugs.	✓	✓	✓			
XE71 ^{1&2}	MC20700970	May be used with all Multi Zones: Cassette, Floor-Ceiling, Slim Duct models - programmable controller with touch pad & back light. Includes 26 ft. wire harness Part # 4003800101 with Molex plugs.	✓	✓	✓			
XE72 ^{1&2}	MC20701210	<u>WIFI</u> for all Multi Zones: Cassette, Floor-Ceiling, Slim Duct models - programmable controller with touch pad & back light. Includes (1) 26 ft. & (1) 6.5 in. harness Part # 4003800101 & 4001024512 with Molex plugs.	✓	✓	✓			
XK41 (Obsolete) (Replaced by XE71)	GREEMC207059	May be used with all Multi Zones-Cassette, Floor-Ceiling, Slim Duct models- programmable controller with touch pad & back light. Includes 26 ft. wire harness Part # 4003800101 with Molex plugs.	✓	✓	✓			
XK76 ³	MC20700360	Single/Multi zone high wall programmable controller with touch pad. Includes (1) 26 ft. & (1) 6.5 in. wire harness Part # 4003800101 & 4001024512 with Molex plugs.	✓	✓	✓			
XK60 ⁴	MC20700550	U-Match & U-Match+ programmable controller with buttons & back light. Requires field supplied 18/2 AWG 300V [min] stranded wire. Max effective wire length is 26 ft.					✓	



Controller Included with Unit

Note: All Wired Controller wire harness is 26 ft., 26 ft. is the maximum length for effective operation. It should not be cut or spliced.

¹ XE71 May be used in lieu of the XK19, but, if used to replace an XK19 already installed the wire harness must also be replaced.

² XE 71 & 72 have integrated control capability for up to 16 units, requires connection to a CE52 Smart Zone Controller.

³ XK76 Used with DUCT B models can be used to set external static pressure / Has integrated control capability for up to 16 units, requires connection to a CE52 Smart Zone Controller.

⁴ XK60 Can be used with UMAT BD hi-static duct models to set external static pressure / Has integrated control capability for up to 16 units, requires connection to a CE52 Smart Zone Controller.

* REPRESENTATIVE IMAGES, ACTUAL PRODUCT MAY VARY, CHECK SALES LITERATURE.

Go to GreeComfort.com <https://www.greecomfort.com/resources/dealer-resources-current-product/>, see **Wired Programmable Controllers** Section for more information.