




## SUBMITTAL DATA

GMV-ND07T/E-T(U) for use with VRF Outdoor Unit  
7000 BTU/H 360 Compact Ceiling Cassette

Job Name	Location	Date
Purchaser	Engineer	
Submitted to	For	
Unit Designation	Schedule No.	

 <p>YAP1F</p>	 <p>GMV-ND07T/E-T(U)</p>	 <p>XK46 (Optional)</p>
--	---	--

### GENERAL FEATURES

- 360° Air Supply
- Independent Swing Control
- New Air Duct and Blade Design for Low Noise
- DC Quiet Drainage Pump
- Wireless Remote with LCD Display
- Wired Controller Options
- Based on Outdoor Unit Performance
- Coil (Indoor and Outdoor) Copper Tube / Aluminum Fin
- Blue Colored Fin - 500 Hrs Salt Spray Tested

## SPECIFICATIONS, FEATURES & FUNCTION SUMMARY



SPECIFICATIONS		GMV-ND07T/E-T(U)		FEATURES & FUNCTIONS SUMMARY		GMV-ND07T/E-T(U)			
System Type		HEAT PUMP							
<b>SYSTEM PERFORMANCE</b>				<b>SYSTEM FEATURES</b>					
Cooling	Nominal	Btu/h	7500	Wired Controller Interface	Yes				
	Capacity @95°F	Btu/h		WiFi Included	No				
Heating	Nominal	Btu/h	8500	NEW! Easy Service Access	Yes				
	Capacity @5°F	Btu/h		Indoor Fan Type	Centrifugal				
	Capacity @17°F	Btu/h		Multi Fan Speeds	3 Speeds				
	Capacity @47°F	W		Indoor Unit Display	No				
SEER2				Auxiliary Electrical Heater	No				
EER2				Ventilation (Outdoor Air)	No				
HSPF2				<b>REMOTE CONTROLLER FUNCTIONS</b>					
COP @5°F	System Performance Based on the Connected Outdoor Unit Performance			Auto Mode	Yes				
COP @47°F				Auto Fan	Yes				
Cooling Temperature Range				°F		Auto Swing (Horizontal Auto Swing)	No		
Heating Temperature Range				°F		Auto Swing - 180° (Vertical Auto Swing)	Yes		
Refrigerant Type						R410A	Clock	Yes	
<b>INDOOR UNIT</b>		<b>GMV-ND07T/E-T(U)</b>		Dry Mode	Yes				
Air flow (Min-Max)	CFM	220 - 295		Dry Anti-Mildew (X-Fan) Mode	Yes				
Sound Pressure Level (Min - Max)	dB(A)	25 - 36		Energy Saving Mode	Yes				
Condensate Drain Size (OD)	in	1		Dirty Filter Alert	No				
External Dimensions (WxHxD)	in	22-7/16 x 10-7/16 x 22-7/16		Fan Speed Control	Yes				
Package Dimension (W x H x D)	in	27-1/2 x 11-5/8 x 25-11/16		I Feel Function	Yes				
Net Weight	lbs	38.6		Privacy Lock	Yes				
Gross Weight	lbs	49.6		Quiet Mode	Yes				
<b>CASSETTE GRILLE (REQUIRED)</b>		<b>TF05</b>		Room Temperature Display	No				
Grille Dimension (W x H x D)	in	24-3/8 x 1-7/8 x 24-3/8		Sleep Mode	Yes				
Package Dimension (W x H x D)	in	27-5/8 x 5 x 27-5/8		3 Sleep Mode Options	Yes				
Weight (Net / Gross)	lbs	6.6 / 10		Timer Mode	Yes				
<b>REFRIGERANT PIPING</b>				Turbo Mode	Yes				
Line Set Sized by the Indoor Unit (Liquid - Gas)	in	1/4 - 3/8		Display On/Off Control	Yes				
<b>ELECTRICAL</b>				Freeze Guard Mode	Yes				
Power Supply	208-230V / 1Ph / 60Hz (Powered by the Outdoor Unit)			Power Failure Mode	Yes				
MCA	A	0.7							
MOCP	A	15							

# DIMENSIONS & CLEARANCES

## INDOOR UNIT


Unit: inch

GMV-ND07T/E-T(U)	
DIMENSIONS	
A	26-3/8
B	23-1/2
C	23-5/16
D	22-1/2
E	5-11/16
F	9-1/2



## INDOOR UNIT

Minimum clearance



Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.