

208~230V Air Handler


Model:GMV-ND42A/A-T(U)



Specifications	Unit	Parameter
Model	—	GMV-ND42A/A-T(U)
Performance		
Rated Cooling Capacity	kBtu/h	42
Rated Heating Capacity	kBtu/h	47
Sound Pressure Level	dB(A)	46/48/50
Electrical Data		
Power Supply	Voltage,Phase, Hertz	208/230,1,60
Maximum Overcurrent Protection (MOP)	A	15
Minimum Circuit Amps (MCA)	A	3.375
Fan		
Type × Quantity	—	Centrifugal ×1
Air Flow Volume	CFM	1118/1265/1441
ESP	Pa	37/0~100
Fan Motor Running Current	A	2.7
Fan Motor Power Output	W	367.5
Refrigerant Piping		
Connection Pipe	Gas(mm/inch)	Φ15.9/Φ5/8
	Liquid(mm/inch)	Φ9.52/Φ3/8
Connection method	—	Brazing Connection
Refrigerant	—	R410A
Dimension/Weight		
Dimensions (H×W×D)	mm/inch	1224×540×540/ (48-1/4×21-1/4×21-1/4)
Net Weight	kg/lbs	67/148
Other		
Safety Certification	—	ETL

Job Name:		Date:	
System Reference No.:			
Engineer Signature:			

Outline and Physical Dimensions of GMV-ND42A/A-T(U).



Unit:mm(in.)

