



EXTENDED RATINGS

Cooling Performance

FXU24HP230V1R32AH / FXU24HP230V1R32AO

FXU36HP230V1R32AH / FXU36HP230V1R32AO

FXU48HP230V1R32AH / FXU48HP230V1R32AO

FXU60HP230V1R32AH / FXU60HP230V1R32AO

Heating Performance

FXU24HP230V1R32AH / FXU24HP230V1R32AO

FXU36HP230V1R32AH / FXU36HP230V1R32AO

FXU48HP230V1R32AH / FXU48HP230V1R32AO

FXU60HP230V1R32AH / FXU60HP230V1R32AO

Thank you for choosing our product.
Please go through this Extended Ratings to design
your project and retain it for future reference.

To download an electric version visit
<https://www.greecomfort.com/our-products/flexx-ultra-r32/>

EXTENDED RATINGS

FXU24HP230V1R32AH / FXU24HP230V1R32AO

COOLING PERFORMANCE

Outdoor Ambient Temperature (DB)		Return Air Temperature																			
		70°F (DB) / 59°F (WB)					75°F (DB) / 63°F (WB)					80°F (DB) / 67°F (WB)					90°F (DB) / 73°F (WB)				
		TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)
MAX OUTPUT*	-20°F																				
	-15°F																				
	-10°F																				
	-5°F																				
	0°F																				
	5°F	21120	14361.6	68.00%	5.98	1035	22560	15566	69.00%	6.12	1079.61	24000	16800	70.00%	6.32	1113	26400	18744	71.00%	6.56	1179.78
	10°F	21120	14361.6	68.00%	5.81	1065	22560	15566	69.00%	5.95	1110.46	24000	16800	70.00%	6.14	1145	26400	18744	71.00%	6.38	1213.49
	15°F	21120	14572.8	69.00%	5.66	1094	22560	15792	70.00%	5.79	1141.3	24000	17040	71.00%	5.98	1177	26400	19008	72.00%	6.20	1247.2
	20°F	21120	14784	70.00%	5.51	1124	22560	16018	71.00%	5.64	1172.15	24000	17280	72.00%	5.82	1208	26400	19272	73.00%	6.04	1280.9
	25°F	21120	14784	70.00%	5.37	1153	22560	16018	71.00%	5.50	1202.99	24000	17280	72.00%	5.67	1240	26400	19272	73.00%	5.89	1314.61
	30°F	21120	14784	70.00%	5.23	1183	22560	16018	71.00%	5.36	1233.84	24000	17280	72.00%	5.53	1272	26400	19272	73.00%	5.74	1348.32
	35°F	21120	14995.2	71.00%	5.10	1213	22560	16243	72.00%	5.23	1264.69	24000	17520	73.00%	5.39	1304	26400	19536	74.00%	5.60	1382.03
	40°F	21120	14995.2	71.00%	4.98	1242	22560	16243	72.00%	5.10	1295.53	24000	17520	73.00%	5.27	1336	26400	19536	74.00%	5.47	1415.74
	45°F	21120	15206.4	72.00%	4.87	1272	22560	16469	73.00%	4.98	1326.38	24000	17760	74.00%	5.14	1367	26400	19800	75.00%	5.34	1449.44
	50°F	21120	15206.4	72.00%	4.76	1301	22560	16469	73.00%	4.87	1357.22	24000	17760	74.00%	5.03	1399	26400	19800	75.00%	5.22	1483.15
	55°F	21120	15206.4	72.00%	4.65	1331	22560	16469	73.00%	4.76	1388.07	24000	17760	74.00%	4.92	1431	26400	19800	75.00%	5.10	1516.86
	60°F	21120	15417.6	73.00%	4.55	1360	22560	16694	74.00%	4.66	1418.92	24000	18000	75.00%	4.81	1463	26400	20064	76.00%	4.99	1550.57
	65°F	21120	15417.6	73.00%	4.45	1390	22560	16694	74.00%	4.56	1449.76	24000	18000	75.00%	4.71	1495	26400	20064	76.00%	4.88	1584.28
	70°F	21120	15628.8	74.00%	4.36	1420	22560	16920	75.00%	4.47	1480.61	24000	18240	76.00%	4.61	1526	26400	20328	77.00%	4.78	1617.98
	75°F	21120	15629	74.00%	4.27	1449	22560	16920	75.00%	4.37	1511.45	24000	18240	76.00%	4.51	1558	26400	20328	77.00%	4.68	1651.69
80°F	21120	15628.8	74.00%	4.19	1479	22560	16920	75.00%	4.29	1542.3	24000	18240	76.00%	4.42	1590	26400	20328	77.00%	4.59	1685.4	
85°F	21120	15628.8	74.00%	3.82	1621	22560	16920	75.00%	3.91	1691.03	24000	18240	76.00%	4.03	1743	26400	20328	77.00%	4.19	1847.93	
90°F	21120	15840	75.00%	3.51	1764	22560	17146	76.00%	3.59	1839.77	24000	18480	77.00%	3.71	1897	26400	20592	78.00%	3.85	2010.47	
95°F	21120	15840	75.00%	3.25	1907	22560	17146	76.00%	3.33	1988.5	24000	18480	77.00%	3.43	2050	26400	20592	78.00%	3.56	2173	
100°F	21120	15840	75.00%	3.15	1964	22560	17146	76.00%	3.23	2048.16	24000	18480	77.00%	3.33	2112	26400	20592	78.00%	3.46	2238.19	
105°F	21120	16051.2	76.00%	3.06	2021	22560	17371	77.00%	3.14	2107.81	24000	18720	78.00%	3.24	2173	26400	20856	79.00%	3.36	2303.38	
110°F	21120	16051.2	76.00%	3.01	2059	22560	17371	77.00%	3.08	2147.58	24000	18720	78.00%	3.18	2214	26400	20856	79.00%	3.30	2346.84	
115°F	20275.2	15611.9	77.00%	2.69	2212	21657.6	16893	78.00%	2.75	2306.66	23040	18201.6	79.00%	2.84	2378	25344	20275.2	80.00%	2.95	2520.68	
120°F	19641.6	15124	77.00%	2.54	2269	20980.8	16365	78.00%	2.60	2366.32	22320	17632.8	79.00%	2.68	2440	24552	19641.6	80.00%	2.78	2585.87	
125°F	18796.8	14661.5	78.00%	2.31	2383	20078.4	15862	79.00%	2.37	2485.63	21360	17088	80.00%	2.44	2563	23496	19031.8	81.00%	2.54	2716.25	
129°F	17952	14002.6	78.00%	2.12	2478	19176	15149	79.00%	2.17	2585.05	20400	16320	80.00%	2.24	2665	22440	18176.4	81.00%	2.33	2824.9	

*Maximum Output values are not based on AHRI test conditions

- LEGEND:** W - Watts
 DB - Dry Bulb
 TC - Total Capacity
 SC - Total Capacity
 SHR - Sensible Heat Ratio
 COP - Coefficient of Performance



[Back to main page](#)

HEATING PERFORMANCE

Outdoor Ambient Temperature		Return Air Temperature									
		70°F (DB)			75°F (DB)			80°F (DB)			
		TC (Btu/h)	COP(W/W)	Power Input (W)	TC (Btu/h)	COP(W/W)	Power Input (W)	TC (Btu/h)	COP(W/W)	Power Input (W)	
MAX OUTPUT*	DB	WB									
	-22°F	-22.5°F	18000	1.49	3550	17640	1.43	3621	17287	1.39	3657
	-20°F	-20.5°F	19500	1.53	3740	19110	1.47	3815	18728	1.42	3852
	-15°F	-16°F	21000	1.57	3930	20580	1.50	4009	20168	1.46	4048
	-10°F	-11°F	22500	1.60	4120	22050	1.54	4202	21609	1.49	4244
	-5°F	-6°F	24000	1.63	4310	23520	1.57	4396	23050	1.52	4439
	0°F	-1°F	24000	1.71	4105	23520	1.65	4187	23050	1.60	4228
	5°F	3°F	24000	1.80	3900	23520	1.73	3978	23050	1.68	4017
	10°F	8°F	24000	1.90	3694	23520	1.83	3768	23050	1.78	3805
	15°F	13°F	24000	2.02	3489	23520	1.94	3559	23050	1.88	3594
	17°F	15°F	24000	2.14	3283	23520	2.06	3349	23050	2.00	3382
	20°F	17°F	24000	2.29	3078	23520	2.20	3139	23050	2.13	3170
	25°F	22°F	24000	2.45	2872	23520	2.35	2930	23050	2.28	2958
	30°F	27°F	24000	2.64	2667	23520	2.53	2720	23050	2.46	2747
	35°F	33°F	24000	2.86	2461	23520	2.75	2510	23050	2.66	2535
	40°F	36°F	24000	3.12	2256	23520	3.00	2301	23050	2.91	2323
	45°F	41°F	24000	3.43	2050	23520	3.30	2091	23050	3.20	2112
	47°F	43°F	24000	3.52	2000	23520	3.38	2040	23050	3.28	2060
	50°F	46°F	25200	3.77	1960	24696	3.62	1999	24202	3.51	2019
	55°F	50°F	26400	4.03	1920	25872	3.87	1958	25355	3.76	1978
60°F	55°F	27000	4.30	1840	26460	4.13	1877	25931	4.01	1895	
65°F	60°F	27000	4.50	1760	26460	4.32	1795	25931	4.19	1813	
70°F	64°F	27000	4.71	1680	26460	4.53	1714	25931	4.39	1730	
75°F	69°F	27000	4.95	1600	26460	4.75	1632	25931	4.61	1648	
80°F	74°F										
86°F	80°F										

*Maximum Output values are not based on AHRI test conditions

LEGEND: W - Watts

- DB - Dry Bulb
- TC - Total Capacity
- SC - Total Capacity
- SHR - Sensible Heat Ratio
- COP - Coefficient of Performance



COOLING PERFORMANCE

Outdoor Ambient Temperature (DB)	Return Air Temperature																				
	70°F (DB) / 59°F (WB)					75°F (DB) / 63°F (WB)					80°F (DB) / 67°F (WB)					90°F (DB) / 73°F (WB)					
	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)	
MAX OUTPUT*	-20°F																				
	-15°F																				
	-10°F																				
	-5°F																				
	0°F																				
	5°F	31680	21542.4	68.00%	5.97	1556	33840	23350	69.00%	6.11	1622.81	36000	25200	70.00%	6.31	1673	39600	28116	71.00%	6.54	1773.38
	10°F	31680	21542.4	68.00%	5.80	1600	33840	23350	69.00%	5.94	1669.18	36000	25200	70.00%	6.13	1721	39600	28116	71.00%	6.36	1824.05
	15°F	31680	21542.4	68.00%	5.64	1645	33840	23350	69.00%	5.78	1715.54	36000	25200	70.00%	5.97	1769	39600	28116	71.00%	6.19	1874.72
	20°F	31680	21542.4	68.00%	5.50	1689	33840	23350	69.00%	5.63	1761.91	36000	25200	70.00%	5.81	1816	39600	28116	71.00%	6.03	1925.38
	25°F	31680	21542.4	68.00%	5.36	1734	33840	23350	69.00%	5.48	1808.27	36000	25200	70.00%	5.66	1864	39600	28116	71.00%	5.87	1976.05
	30°F	31680	21542.4	68.00%	5.22	1778	33840	23350	69.00%	5.35	1854.64	36000	25200	70.00%	5.52	1912	39600	28116	71.00%	5.73	2026.72
	35°F	31680	21542.4	68.00%	5.09	1823	33840	23350	69.00%	5.22	1901.01	36000	25200	70.00%	5.38	1960	39600	28116	71.00%	5.59	2077.39
	40°F	31680	21542.4	68.00%	4.97	1867	33840	23350	69.00%	5.09	1947.37	36000	25200	70.00%	5.26	2008	39600	28116	71.00%	5.45	2128.06
	45°F	31680	21542.4	68.00%	4.86	1912	33840	23350	69.00%	4.97	1993.74	36000	25200	70.00%	5.13	2055	39600	28116	71.00%	5.33	2178.72
	50°F	31680	22176	70.00%	4.75	1956	33840	24026	71.00%	4.86	2040.1	36000	25920	72.00%	5.02	2103	39600	28908	73.00%	5.21	2229.39
	55°F	31680	22176	70.00%	4.64	2000	33840	24026	71.00%	4.75	2086.47	36000	25920	72.00%	4.91	2151	39600	28908	73.00%	5.09	2280.06
	60°F	31680	22492.8	71.00%	4.54	2045	33840	24365	72.00%	4.65	2132.84	36000	26280	73.00%	4.80	2199	39600	29304	74.00%	4.98	2330.73
	65°F	31680	22492.8	71.00%	4.44	2089	33840	24365	72.00%	4.55	2179.2	36000	26280	73.00%	4.70	2247	39600	29304	74.00%	4.87	2381.4
	70°F	31680	22809.6	72.00%	4.35	2134	33840	24703	73.00%	4.46	2225.57	36000	26640	74.00%	4.60	2294	39600	29700	75.00%	4.77	2432.06
	75°F	31680	22810	72.00%	4.26	2178	33840	24703	73.00%	4.37	2271.93	36000	26640	74.00%	4.50	2342	39600	29700	75.00%	4.67	2482.73
80°F	31680	22809.6	72.00%	4.18	2223	33840	24703	73.00%	4.28	2318.3	36000	26640	74.00%	4.41	2390	39600	29700	75.00%	4.58	2533.4	
85°F	31093.3	22387.2	72.00%	3.79	2406	33213.3	24246	73.00%	3.88	2509.07	35333.3	26146.7	74.00%	4.00	2587	38866.7	29150	75.00%	4.15	2741.87	
90°F	30506.7	22269.9	73.00%	3.45	2589	32586.7	24114	74.00%	3.54	2699.83	34666.7	26000	75.00%	3.65	2783	38133.3	28981.3	76.00%	3.79	2950.33	
95°F	29920	21841.6	73.00%	3.16	2771	31960	23650	74.00%	3.24	2890.6	34000	25500	75.00%	3.34	2980	37400	28424	76.00%	3.47	3158.8	
100°F	29920	21841.6	73.00%	3.07	2855	31960	23650	74.00%	3.15	2977.32	34000	25500	75.00%	3.25	3069	37400	28424	76.00%	3.37	3253.56	
105°F	29920	22140.8	74.00%	2.99	2938	31960	23970	75.00%	3.06	3064.04	34000	25840	76.00%	3.15	3159	37400	28798	77.00%	3.27	3348.33	
110°F	28723.2	21255.2	74.00%	2.81	2993	30681.6	23011	75.00%	2.88	3121.85	32640	24806.4	76.00%	2.97	3218	35904	27646.1	77.00%	3.08	3411.5	
115°F	27526.4	20644.8	75.00%	2.51	3215	29403.2	22346	76.00%	2.57	3353.1	31280	24085.6	77.00%	2.65	3457	34408	26838.2	78.00%	2.75	3664.21	
120°F	25432	19074	75.00%	2.26	3298	27166	20646	76.00%	2.31	3439.81	28900	22253	77.00%	2.39	3546	31790	24796.2	78.00%	2.48	3758.97	
125°F	23636.8	17964	76.00%	2.00	3464	25248.4	19441	77.00%	2.05	3613.25	26860	20950.8	78.00%	2.11	3725	29546	23341.3	79.00%	2.19	3948.5	
129°F	21542.4	16372.2	76.00%	1.75	3603	23011.2	17719	77.00%	1.79	3757.78	24480	19094.4	78.00%	1.85	3874	26928	21273.1	79.00%	1.92	4106.44	

*Maximum Output values are not based on AHRI test conditions

- LEGEND:** W - Watts
 DB - Dry Bulb
 TC - Total Capacity
 SC - Total Capacity
 SHR - Sensible Heat Ratio
 COP - Coefficient of Performance



[Back to main page](#)

HEATING PERFORMANCE

Outdoor Ambient Temperature		Return Air Temperature									
		70°F (DB)			75°F (DB)			80°F (DB)			
		TC (Btu/h)	COP(W/W)	Power Input (W)	TC (Btu/h)	COP(W/W)	Power Input (W)	TC (Btu/h)	COP(W/W)	Power Input (W)	
MAX OUTPUT*	DB	WB									
	-22°F	-22.5°F	20400	1.31	4550	19992	1.26	4641	19592	1.23	4687
	-20°F	-20.5°F	22325	1.41	4638	21879	1.36	4731	21441	1.32	4778
	-15°F	-16°F	24250	1.50	4727	23765	1.44	4821	23290	1.40	4869
	-10°F	-11°F	26175	1.59	4815	25652	1.53	4912	25139	1.49	4960
	-5°F	-6°F	28101	1.68	4904	27539	1.61	5002	26988	1.57	5051
	0°F	-1°F	30039	1.72	5112	29438	1.52	5668	28849	1.48	5724
	5°F	3°F	32300	1.80	5260	31654	1.73	5365	31021	1.68	5418
	10°F	8°F	34000	1.99	5006	33320	1.91	5106	32654	1.86	5156
	15°F	13°F	34000	2.10	4751	33320	2.02	4846	32654	1.96	4894
	17°F	15°F	34000	2.22	4497	33320	2.13	4587	32654	2.07	4632
	20°F	17°F	34000	2.35	4242	33320	2.26	4327	32654	2.19	4369
	25°F	22°F	34000	2.50	3988	33320	2.40	4068	32654	2.33	4107
	30°F	27°F	34000	2.67	3733	33320	2.56	3808	32654	2.49	3845
	35°F	33°F	34000	2.86	3479	33320	2.75	3548	32654	2.67	3583
	40°F	36°F	34000	3.09	3224	33320	2.97	3289	32654	2.88	3321
	45°F	41°F	34000	3.36	2970	33320	3.22	3029	32654	3.13	3059
	47°F	43°F	34000	3.30	3020	33320	3.17	3080	32654	3.08	3111
	50°F	46°F	34340	3.40	2960	33653	3.27	3019	32980	3.17	3048
	55°F	50°F	34680	3.51	2899	33986	3.37	2957	33307	3.27	2986
60°F	55°F	35020	3.69	2778	34320	3.55	2834	33633	3.44	2862	
65°F	60°F	35360	3.90	2658	34653	3.75	2711	33960	3.64	2737	
70°F	64°F	35700	4.12	2537	34986	3.96	2588	34286	3.85	2613	
75°F	69°F	36040	4.37	2416	35319.2	4.20	2464.32	34613	4.08	2488	
80°F	74°F										
86°F	80°F										

*Maximum Output values are not based on AHRI test conditions

LEGEND: W - Watts

- DB - Dry Bulb
- TC - Total Capacity
- SC - Total Capacity
- SHR - Sensible Heat Ratio
- COP - Coefficient of Performance



COOLING PERFORMANCE

Outdoor Ambient Temperature (DB)		Return Air Temperature																			
		70°F (DB) / 59°F (WB)					75°F (DB) / 63°F (WB)					80°F (DB) / 67°F (WB)					90°F (DB) / 73°F (WB)				
		TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)
MAX OUTPUT*	-20°F																				
	-15°F																				
	-10°F																				
	-5°F																				
	0°F																				
	5°F	41800	28424	68.00%	5.27	2324	44650	30809	69.00%	5.40	2424.03	47500	33250	70.00%	5.57	2499	52250	37097.5	71.00%	5.78	2648.94
	10°F	42240	28723.2	68.00%	5.18	2390	45120	31133	69.00%	5.30	2493.29	48000	33600	70.00%	5.47	2570	52800	37488	71.00%	5.68	2724.62
	15°F	42680	29022.4	68.00%	5.09	2457	45590	31457	69.00%	5.21	2562.55	48500	33950	70.00%	5.38	2642	53350	37878.5	71.00%	5.58	2800.31
	20°F	43120	29321.6	68.00%	5.01	2523	46060	31781	69.00%	5.13	2631.8	49000	34300	70.00%	5.29	2713	53900	38269	71.00%	5.49	2875.99
	25°F	43560	29620.8	68.00%	4.93	2590	46530	32106	69.00%	5.05	2701.06	49500	34650	70.00%	5.21	2785	54450	38659.5	71.00%	5.41	2951.68
	30°F	44000	29920	68.00%	4.86	2656	47000	32430	69.00%	4.97	2770.32	50000	35000	70.00%	5.13	2856	55000	39050	71.00%	5.32	3027.36
	35°F	44000	29920	68.00%	4.74	2722	47000	32430	69.00%	4.85	2839.58	50000	35000	70.00%	5.01	2927	55000	39050	71.00%	5.19	3103.04
	40°F	44000	29920	68.00%	4.62	2789	47000	32430	69.00%	4.74	2908.84	50000	35000	70.00%	4.89	2999	55000	39050	71.00%	5.07	3178.73
	45°F	44000	29920	68.00%	4.52	2855	47000	32430	69.00%	4.63	2978.09	50000	35000	70.00%	4.77	3070	55000	39050	71.00%	4.95	3254.41
	50°F	44000	30800	70.00%	4.41	2922	47000	33370	71.00%	4.52	3047.35	50000	36000	72.00%	4.66	3142	55000	40150	73.00%	4.84	3330.1
	55°F	44000	30800	70.00%	4.32	2988	47000	33370	71.00%	4.42	3116.61	50000	36000	72.00%	4.56	3213	55000	40150	73.00%	4.73	3405.78
	60°F	44000	31240	71.00%	4.22	3054	47000	33840	72.00%	4.32	3185.87	50000	36500	73.00%	4.46	3284	55000	40700	74.00%	4.63	3481.46
	65°F	44000	31240	71.00%	4.13	3121	47000	33840	72.00%	4.23	3255.13	50000	36500	73.00%	4.37	3356	55000	40700	74.00%	4.53	3557.15
	70°F	44000	31680	72.00%	4.05	3187	47000	34310	73.00%	4.14	3324.38	50000	37000	74.00%	4.28	3427	55000	41250	75.00%	4.44	3632.83
	75°F	44000	31680	72.00%	3.96	3254	47000	34310	73.00%	4.06	3393.64	50000	37000	74.00%	4.19	3499	55000	41250	75.00%	4.35	3708.52
80°F	44000	31680	72.00%	3.88	3320	47000	34310	73.00%	3.98	3462.9	50000	37000	74.00%	4.10	3570	55000	41250	75.00%	4.26	3784.2	
85°F	43413.3	31257.6	72.00%	3.63	3506	46373.3	33853	73.00%	3.72	3656.9	49333.3	36506.7	74.00%	3.84	3770	54266.7	40700	75.00%	3.98	3996.2	
90°F	42826.7	31263.5	73.00%	3.40	3692	45746.7	33853	74.00%	3.48	3850.9	48666.7	36500	75.00%	3.59	3970	53533.3	40685.3	76.00%	3.73	4208.2	
95°F	42240	30835.2	73.00%	3.19	3878	45120	33389	74.00%	3.27	4044.9	48000	36000	75.00%	3.37	4170	52800	40128	76.00%	3.50	4420.2	
100°F	42240	30835.2	73.00%	3.10	3994	45120	33389	74.00%	3.17	4166.25	48000	36000	75.00%	3.28	4295	52800	40128	76.00%	3.40	4552.81	
105°F	42240	31257.6	74.00%	3.01	4111	45120	33840	75.00%	3.08	4287.59	48000	36480	76.00%	3.18	4420	52800	40656	77.00%	3.30	4685.41	
110°F	41817.6	30945	74.00%	2.93	4188	44668.8	33502	75.00%	3.00	4368.49	47520	36115.2	76.00%	3.09	4504	52272	40249.4	77.00%	3.21	4773.82	
115°F	40128	30096	75.00%	2.61	4499	42864	32577	76.00%	2.68	4692.08	45600	35112	77.00%	2.76	4837	50160	39124.8	78.00%	2.87	5127.43	
120°F	38438.4	28828.8	75.00%	2.44	4615	41059.2	31205	76.00%	2.50	4813.43	43680	33633.6	77.00%	2.58	4962	48048	37477.4	78.00%	2.68	5260.04	
125°F	36748.8	27929.1	76.00%	2.22	4848	39254.4	30226	77.00%	2.28	5056.13	41760	32572.8	78.00%	2.35	5213	45936	36289.4	79.00%	2.44	5525.25	
129°F	33792	25681.9	76.00%	1.96	5042	36096	27794	77.00%	2.01	5258.37	38400	29952	78.00%	2.08	5421	42240	33369.6	79.00%	2.15	5746.26	

*Maximum Output values are not based on AHRI test conditions

LEGEND: W - Watts
 DB - Dry Bulb
 TC - Total Capacity
 SC - Total Capacity
 SHR - Sensible Heat Ratio
 COP - Coefficient of Performance



[Back to main page](#)

HEATING PERFORMANCE

Outdoor Ambient Temperature		Return Air Temperature									
		70°F (DB)			75°F (DB)			80°F (DB)			
		TC (Btu/h)	COP(W/W)	Power Input (W)	TC (Btu/h)	COP(W/W)	Power Input (W)	TC (Btu/h)	COP(W/W)	Power Input (W)	
MAX OUTPUT*	DB	WB									
	-22°F	-22.5°F	26200	1.27	6060	25676	1.22	6181	25162	1.18	6242
	-20°F	-20.5°F	29438	1.38	6245	28849	1.33	6369	28272	1.29	6432
	-15°F	-16°F	32675	1.49	6429	32022	1.43	6558	31381	1.39	6622
	-10°F	-11°F	35913	1.59	6614	35194	1.53	6746	34490	1.48	6812
	-5°F	-6°F	39150	1.69	6798	38367	1.62	6934	37600	1.57	7002
	0°F	-1°F	41850	1.73	7103	41013	1.66	7245	40193	1.61	7316
	5°F	3°F	45000	1.80	7320	44100	1.73	7466	43218	1.68	7540
	10°F	8°F	48000	2.01	6990	47040	1.93	7130	46099	1.88	7200
	15°F	13°F	48000	2.11	6660	47040	2.03	6793	46099	1.97	6860
	17°F	15°F	48000	2.22	6330	47040	2.14	6457	46099	2.07	6520
	20°F	17°F	48000	2.34	6000	47040	2.25	6120	46099	2.19	6180
	25°F	22°F	48000	2.48	5670	47040	2.38	5783	46099	2.31	5840
	30°F	27°F	48000	2.63	5340	47040	2.53	5447	46099	2.46	5500
	35°F	33°F	48000	2.81	5010	47040	2.70	5110	46099	2.62	5160
	40°F	36°F	48000	3.01	4680	47040	2.89	4774	46099	2.80	4820
	45°F	41°F	48000	3.23	4350	47040	3.11	4437	46099	3.02	4481
	47°F	43°F	48000	3.30	4260	47040	3.17	4345	46099	3.08	4388
	50°F	46°F	48480	3.40	4175	47510	3.27	4258	46560	3.17	4300
	55°F	50°F	48960	3.51	4090	47981	3.37	4171	47021	3.27	4212
60°F	55°F	49440	3.70	3919	48451	3.55	3998	47482	3.45	4037	
65°F	60°F	49920	3.90	3749	48922	3.75	3824	47943	3.64	3861	
70°F	64°F	50400	4.13	3578	49392	3.97	3650	48404	3.85	3686	
75°F	69°F	50880	4.38	3408	49862.4	4.20	3476.16	48865	4.08	3510	
80°F	74°F										
86°F	80°F										

*Maximum Output values are not based on AHRI test conditions

LEGEND: W - Watts

- DB - Dry Bulb
- TC - Total Capacity
- SC - Total Capacity
- SHR - Sensible Heat Ratio
- COP - Coefficient of Performance



COOLING PERFORMANCE

Outdoor Ambient Temperature (DB)	Return Air Temperature																			
	70°F (DB) / 59°F (WB)					75°F (DB) / 63°F (WB)					80°F (DB) / 67°F (WB)					90°F (DB) / 73°F (WB)				
	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)	TC (Btu/h)	SC (Btu/h)	SHR	EER	Power Input (W)
-20°F																				
-15°F																				
-10°F																				
-5°F																				
0°F																				
5°F	46816	31834.9	68.00%	5.07	2708	50008	34506	69.00%	5.19	2824.64	53200	37240	70.00%	5.35	2912	58520	41549.2	71.00%	5.56	3086.72
10°F	47308.8	32170	68.00%	4.98	2786	50534.4	34869	69.00%	5.10	2905.34	53760	37632	70.00%	5.26	2995	59136	41986.6	71.00%	5.46	3174.91
15°F	47801.6	32505.1	68.00%	4.89	2863	51060.8	35232	69.00%	5.01	2986.05	54320	38024	70.00%	5.17	3078	59752	42423.9	71.00%	5.37	3263.1
20°F	48294.4	32840.2	68.00%	4.81	2940	51587.2	35595	69.00%	4.93	3066.75	54880	38416	70.00%	5.09	3162	60368	42861.3	71.00%	5.28	3351.3
25°F	48787.2	33175.3	68.00%	4.74	3018	52113.6	35958	69.00%	4.85	3147.46	55440	38808	70.00%	5.01	3245	60984	43298.6	71.00%	5.20	3439.49
30°F	49280	33510.4	68.00%	4.67	3095	52640	36322	69.00%	4.78	3228.16	56000	39200	70.00%	4.93	3328	61600	43736	71.00%	5.12	3527.68
35°F	49280	33510.4	68.00%	4.55	3172	52640	36322	69.00%	4.66	3308.86	56000	39200	70.00%	4.81	3411	61600	43736	71.00%	4.99	3615.87
40°F	49280	33510.4	68.00%	4.44	3250	52640	36322	69.00%	4.55	3389.57	56000	39200	70.00%	4.70	3494	61600	43736	71.00%	4.87	3704.06
45°F	49280	33510.4	68.00%	4.34	3327	52640	36322	69.00%	4.45	3470.27	56000	39200	70.00%	4.59	3578	61600	43736	71.00%	4.76	3792.26
50°F	49280	34496	70.00%	4.24	3405	52640	37374	71.00%	4.34	3550.98	56000	40320	72.00%	4.48	3661	61600	44968	73.00%	4.65	3880.45
55°F	49280	34496	70.00%	4.15	3482	52640	37374	71.00%	4.25	3631.68	56000	40320	72.00%	4.38	3744	61600	44968	73.00%	4.55	3968.64
60°F	49280	34988.8	71.00%	4.06	3559	52640	37901	72.00%	4.16	3712.38	56000	40880	73.00%	4.29	3827	61600	45584	74.00%	4.45	4056.83
65°F	49280	34988.8	71.00%	3.97	3637	52640	37901	72.00%	4.07	3793.09	56000	40880	73.00%	4.20	3910	61600	45584	74.00%	4.36	4145.02
70°F	49280	35481.6	72.00%	3.89	3714	52640	38427	73.00%	3.98	3873.79	56000	41440	74.00%	4.11	3994	61600	46200	75.00%	4.26	4233.22
75°F	49280	35482	72.00%	3.81	3791	52640	38427	73.00%	3.90	3954.5	56000	41440	74.00%	4.03	4077	61600	46200	75.00%	4.18	4321.41
80°F	49280	35481.6	72.00%	3.73	3869	52640	38427	73.00%	3.82	4035.2	56000	41440	74.00%	3.95	4160	61600	46200	75.00%	4.09	4409.6
85°F	48693.3	35059.2	72.00%	3.48	4101	52013.3	37970	73.00%	3.56	4277.7	55333.3	40946.7	74.00%	3.68	4410	60866.7	45650	75.00%	3.82	4674.6
90°F	48106.7	35117.9	73.00%	3.25	4334	51386.7	38026	74.00%	3.33	4520.2	54666.7	41000	75.00%	3.44	4660	60133.3	45701.3	76.00%	3.57	4939.6
95°F	47520	34689.6	73.00%	3.05	4566	50760	37562	74.00%	3.12	4762.7	54000	40500	75.00%	3.22	4910	59400	45144	76.00%	3.34	5204.6
100°F	47520	34689.6	73.00%	2.96	4703	50760	37562	74.00%	3.03	4905.58	54000	40500	75.00%	3.13	5057	59400	45144	76.00%	3.25	5360.74
105°F	47520	35164.8	74.00%	2.88	4840	50760	38070	75.00%	2.95	5048.46	54000	41040	76.00%	3.04	5205	59400	45738	77.00%	3.16	5516.88
110°F	45619.2	33758.2	74.00%	2.71	4932	48729.6	36547	75.00%	2.78	5143.72	51840	39398.4	76.00%	2.87	5303	57024	43908.5	77.00%	2.97	5620.97
115°F	43718.4	32788.8	75.00%	2.42	5297	46699.2	35491	76.00%	2.48	5524.73	49680	38253.6	77.00%	2.56	5696	54648	42625.4	78.00%	2.65	6037.34
120°F	40392	30294	75.00%	2.18	5434	43146	32791	76.00%	2.23	5667.61	45900	35343	77.00%	2.30	5843	50490	39382.2	78.00%	2.39	6193.47
125°F	37540.8	28531	76.00%	1.93	5708	40100.4	30877	77.00%	1.97	5953.38	42660	33274.8	78.00%	2.04	6138	46926	37071.5	79.00%	2.11	6505.75
129°F	34214.4	26002.9	76.00%	1.69	5936	36547.2	28141	77.00%	1.73	6191.51	38880	30326.4	78.00%	1.79	6383	42768	33786.7	79.00%	1.85	6765.98

MAX OUTPUT *

*Maximum Output values are not based on AHRI test conditions

LEGEND: W - Watts
 DB - Dry Bulb
 TC - Total Capacity
 SC - Total Capacity
 SHR - Sensible Heat Ratio
 COP - Coefficient of Performance



HEATING PERFORMANCE

Outdoor Ambient Temperature		Return Air Temperature									
		70°F (DB)			75°F (DB)			80°F (DB)			
		TC (Btu/h)	COP(W/W)	Power Input (W)	TC (Btu/h)	COP(W/W)	Power Input (W)	TC (Btu/h)	COP(W/W)	Power Input (W)	
MAX OUTPUT*	DB	WB									
	-22°F	-22.5°F	27000	1.27	6240	26460	1.22	6365	25931	1.18	6427
	-20°F	-20.5°F	30150	1.39	6363	29547	1.33	6490	28956	1.29	6554
	-15°F	-16°F	33300	1.50	6486	32634	1.45	6616	31981	1.40	6681
	-10°F	-11°F	36450	1.62	6609	35721	1.55	6741	35007	1.51	6807
	-5°F	-6°F	39600	1.72	6732	38808	1.66	6867	38032	1.61	6934
	0°F	-1°F	42300	1.75	7075	41454	1.49	8161	40625	1.44	8241
	5°F	3°F	45000	1.80	7320	44100	1.54	8410	43218	1.49	8493
	10°F	8°F	45900	1.91	7051	44982	1.64	8031	44082	1.59	8110
	15°F	13°F	46980	2.03	6782	46040	1.76	7652	45120	1.71	7727
	17°F	15°F	48060	2.16	6513	47099	1.90	7273	46157	1.84	7344
	20°F	17°F	49140	2.31	6244	48157	2.05	6894	47194	1.99	6961
	25°F	22°F	50220	2.46	5976	49216	2.21	6515	48231	2.15	6579
	30°F	27°F	51300	2.63	5707	50274	2.40	6135	49269	2.33	6196
	35°F	33°F	52380	2.82	5438	51332	2.61	5756	50306	2.54	5813
	40°F	36°F	53460	3.03	5169	52391	2.86	5377	51343	2.77	5430
	45°F	41°F	54000	3.23	4900	52920	3.10	4998	51862	3.01	5047
	47°F	43°F	54000	3.30	4800	52920	3.17	4896	51862	3.07	4944
	50°F	46°F	54540	3.40	4704	53449	3.26	4798	52380	3.17	4845
	55°F	50°F	55080	3.50	4608	53978	3.37	4700	52899	3.27	4746
60°F	55°F	55620	3.69	4416	54508	3.55	4504	53417	3.44	4548	
65°F	60°F	56160	3.90	4224	55037	3.74	4308	53936	3.63	4351	
70°F	64°F	56700	4.12	4032	55566	3.96	4113	54455	3.84	4153	
75°F	69°F	57240	4.37	3840	56095.2	4.20	3916.8	54973	4.07	3955	
80°F	74°F										
86°F	80°F										

*Maximum Output values are not based on AHRI test conditions

LEGEND: W - Watts

- DB - Dry Bulb
- TC - Total Capacity
- SC - Total Capacity
- SHR - Sensible Heat Ratio
- COP - Coefficient of Performance





Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.

GRECOMFORT.COM