

R32

MULTI

IT ALL FITS TOGETHER
FOR COMFORT



A MULTI-ZONE SYSTEM WITH ALL THE OPTIONS FOR EACH SPACE

GREE's Multi-Zone systems deliver versatility and high performance. With 7 indoor options to choose from, each space is optimally treated for comfort and efficiency.

- UP TO 21.0 SEER2 / 13.6 EER2 / 10.0 HSPF2 EFFICIENCY
- COOLING RANGE -22°F - 118°F
- HEATING RANGE -22°F - 75°F
- MAXIMUM LINE LENGTH: 328 FT.

- Self-Diagnosis
- Indoor units powered by outdoor unit
- Intelligent defrost
- Automatic voltage adaptation
- Small footprint design
- Advanced G10 inverter technology
- Quiet operation
- Up to 7 unique indoor options



SYSTEM TYPE			HEAT PUMP				
Outdoor Model			MUL18HP230V1R32AO	MUL24HP230V1R32AO	MUL30HP230V1R32AO	MUL36HP230V1R32AO	MUL42HP230V1R32AO
Number of Zones			2	2 - 3	2 - 4	2 - 4	2 - 5
SYSTEM PERFORMANCE (Non-Ducted Indoor Units)							
Cooling Capacity	Min - Max	Btu/h	7,300 - 19,800	7,500 - 31,400	8,190 - 34,100	8,870 - 40,900	8,870 - 44,300
	Capacity @95°F	Btu/h	18,000	24,000	28,400	36,000	42,000
Heating Capacity	Min - Max	Btu/h	7,300 - 19,800	7,500 - 31,400	8,190 - 40,900	8,870 - 44,300	8,870 - 46,000
	Capacity @5°F	Btu/h					
	Capacity @17°F	Btu/h					
	Capacity @47°F	Btu/h	18,000	24,000	30,000	36,000	42,000
SEER2			21	21	21	21	21
EER2			12.9	13.3	13.6	12	13.5
HSPF2			10	10	10	10	10
COP @5°F							
COP @47°F			3.9	3.9	4.19	3.56	3.9
SYSTEM PERFORMANCE (Ducted Indoor Units)							
Cooling Capacity	Min - Max	Btu/h	7,300 - 19,800	7,500 - 31,400	8,190 - 34,100	8,870 - 40,900	8,870 - 44,300
	Capacity @95°F	Btu/h					
Heating Capacity	Min - Max	Btu/h	7,300 - 19,800	7,500 - 31,400	8,190 - 40,900	8,870 - 44,300	8,870 - 46,000
	Capacity @5°F	Btu/h					
	Capacity @17°F	Btu/h					
	Capacity @47°F	Btu/h					
SEER2							
EER2							
HSPF2							
COP @5°F							
COP @47°F							
SYSTEM PERFORMANCE (Mixed Ducted and Non-Ducted Indoor Units)							
Cooling Capacity	Min - Max	Btu/h	7,300 - 19,800	7,500 - 31,400	8,190 - 34,100	8,870 - 40,900	8,870 - 44,300
	Capacity @95°F	Btu/h					
Heating Capacity	Min - Max	Btu/h	7,300 - 19,800	7,500 - 31,400	8,190 - 40,900	8,870 - 44,300	8,870 - 46,000
	Capacity @5°F	Btu/h					
	Capacity @17°F	Btu/h					
	Capacity @47°F	Btu/h					
SEER2							
EER2							
HSPF2							
COP @5°F							
COP @47°F							
OUTDOOR UNIT			MUL18HP230V1R32AO	MUL24HP230V1R32AO	MUL30HP230V1R32AO	MUL36HP230V1R32AO	MUL42HP230V1R32AO
Cooling Temperature Range		°F	-22 - 118				
Heating Temperature Range		°F	-22 - 75				
Refrigerant Type			R32				
Sound Pressure Level		dB(A)	54	58	62	63	63
External Dimensions (W x H x D)		in	32-23/64 x 21-42/64 x 13-55/64	37-61/64 x 25-63/64 x 15-53/64	40-10/64 x 32-33/64 x 16-52/64	40-10/64 x 32-33/64 x 16-52/64	40-10/64 x 32-33/64 x 16-52/64
Package Dimension (W x H x D)		in	34-21/64 x 24-13/32 x 15-43/64	40-5/8 x 29-1/64 x 17-61/64	43-1/32 x 34-27/32 x 19-9/16	43-1/32 x 34-27/32 x 19-9/16	43-1/32 x 34-27/32 x 19-9/16
Net Weight		lbs	75.0	112.5	145.5	176.4	178.6
Gross Weight		lbs	81.6	122.4	161.0	189.6	191.8
REFRIGERANT PIPING							
Refrigerant Charge - R410A		oz	31.8	59.98	77.62	95.24	95.24
Additional Charge		oz/ft	0.2	0.2	0.2	0.2	0.2
Port Size (Liquid - Gas)	Port A (in)	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8
	Port B (in)	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8
	Port C (in)		1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8
	Port D (in)			1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8
	Port E (in)				1/4 - 3/8	1/4 - 3/8	1/4 - 3/8
Pre-Charge Length		ft	33	98	131	131	164
Pipe Length (Min - Max)		ft	10 - 131	10 - 197	10 - 263	10 - 263	10 - 328
Pipe Length to furthest Indoor Unit		ft	66	66	82	82	82
Max. Pipe Elevation		ft	49	49	82	82	82
ELECTRICAL							
Power Supply			208-230V / 1Ph / 60Hz				
Voltage Range (Min - Max)		VAC	187 - 253				
Rated Current - Cooling		A	11	14	20	21.7	21.7
Rated Current - Heating		A	11	14.8	21.7	22.6	22.6
MCA		A	18.5	19.5	23	29	29
MOCP		A	20	25	35	35	35
Suggested Breaker Size		A	20	20	25	30	30
Main Power Wire Size		AWG	Per Local Code	Per Local Code	Per Local Code	Per Local Code	Per Local Code
Interconnecting Wire Size		AWG	14 / 4	14 / 4	14 / 4	14 / 4	14 / 4
LIMITED WARRANTY			5 Years Parts, 7 Years Compressor - Residential & Commercial				